

Application No. 09/980696
Page 3

Amendment
Attorney Docket No. H01.2I-10177-US01

Amendments To The Claims:

Please amend the claims as follows:

1. (Currently Amended): An apparatus for mounting ~~and/or dismounting~~ hoses onto ~~or from~~ socket pieces ~~or operations of such a type~~, comprising:

- a drive (2) producing a linear driving motion including a power supply unit and a control unit (3) for controlling the driving motion, a feed member (39) adapted to constructed and arranged to be linearly driven by the drive (2),

- pivotally supported inserted plier halves (24) the inner lever ends (27) of which facing away from a socket piece (52) are engaged by the feed member (39) in order to pivot the inserted plier halves (24) with their jaws (29) against a hose (50) disposed therebetween during a forward motion of the feed member (39),

- a bearing part (23) supporting the inserted plier halves (24) and adapted to constructed and arranged to be displaced in the direction of the feed member including a stop (13^v, 13^{vi}), and

a counterstop (15) connected to the feed member (39) which, after a phase of the forward motion of the feed member (39) required to clamp the hose (50) in place between the jaws (29), hits upon the stop (13^v, 13^{vi}) while carrying along the bearing part (23) through the remaining phase of the forward motion in order to advance the inserted plier halves (24) and to push the hose (50) clamped therein onto or from a socket piece (52).

2. (Currently amended): The apparatus according to claim 1, including an end support (34) for being stayed on a socket piece (52) ~~and/or a structure carrying the socket piece (52) and/or a structure having a stable position with respect to the socket piece (52)~~ and for absorbing the reaction forces produced by pushing the hose (50) onto ~~and/or from~~ the socket piece (52).

Application No. 09/980696
Page 4

Amendment
Attorney Docket No. H01.2I-10177-US01

3. (Previously presented): The apparatus according to claim 1 wherein the drive (2) has at least one driving piston (41, 55) which is connected to a pressurized-medium connection via a pressurized-medium valve.

4. (Original): The apparatus according to claim 3 wherein the drive has a spring mechanism (42, 59) for moving back the driving pistons (41, 55) in case of pressure relief.

5. (Previously presented): The apparatus according to claim 1 wherein there is another spring mechanism between the inserted plier halves (24) for pivoting the inserted plier halves (24) away from each other.

6. (Previously presented): The apparatus according to claim 1 wherein the forward motion of the feed member (39) is directed away from the drive (2).

7. (Original): The apparatus according to claim 6 wherein the inserted plier halves (24) with their jaws (19) are disposed between the drive (2) and the end support (34').

8. (Previously presented): The apparatus according to claim 1 wherein the forward motion of the feed member (39) is directed towards the drive (2).

9. (Original): The apparatus according to claim 8 wherein the end support (34') is disposed between the drive (2) and the jaws (29) of the inserted plier halves (24).

Application No. 09/980696
Page 5

Amendment
Attorney Docket No. H01.2I-10177-US01

10. (Previously presented): The apparatus according to claim 1 wherein the feed member (39) has chamfers (39) which interact with the inner lever ends (27).

11. (Previously presented): The apparatus according to claim 1 wherein the inner lever ends carry rotatably supported rollers (27) the circumference of which is engaged by the feed member (39).

12. (Previously presented): The apparatus according to claim 1 wherein the inserted plier halves (24) each are substantially of a Z shape, each of them being pivotally disposed, with a first outer leg (25), in a plane containing the axis of motion of the feed member (39) and, with a second outer leg (29) forming one jaw, are disposed in a second plane parallel with the first one.

13. (Previously presented): The apparatus according to claim 1 wherein the jaws (29) of the inserted plier halves (24) each form a partially cylindrical receptacle (30) for a portion of the hose (50).

14. (Currently amended): The apparatus according to claim 13 wherein the receptacles (30) of the jaws (29) have an undersize with regard to the cross-section of the hose (50) to be accommodated ~~and/or with respect to a nozzle (51) at the end of the hose (50).~~

15. (Previously presented): The apparatus according to claim 13 wherein the jaws (29) have locking surfaces (30) for clamping the hose (50) in place, which are rigid in a portion (31) which is farther way from the end support (34) and are elastic in a portion (32) which is closer to the end support (34) for pushing a clamped hose (50) over and onto a hose nozzle (52).

Application No. 09/980696
Page 6

Amendment
Attorney Docket No. H01.2I-10177-US01

16. (Currently amended): The apparatus according to claim 15 wherein the rigid portion (32) of the locking surfaces (30), along with the inserted plier halves (24), is integrally formed from rigid material ~~and/or the elastic portion (52) of the locking surfaces (30) is formed from an elastic material introduced into the inserted plier halves (24).~~

17. (Original): The apparatus according to claim 16 wherein the elastic portion (52) of the locking surfaces (30) is formed by sleeve segments introduced into the jaws (29).

18. (Currently Amended): The apparatus according to claim 1 wherein the jaws on the locking surfaces (30) have a structure ~~and/or roughened surface~~ that enhance friction.

19. (Previously presented): The apparatus according to claim 1 wherein the bearing part (23) has two parallel-arranged slide blocks (13) which are guided in slideblock guides (10) and are interconnected by bolts (14, 15) on which the inserted plier halves (24) are supported between the slide blocks (13).

20. (Original): The apparatus according to claim 19 wherein the slide blocks (13) are of a panel shape.

21. (Previously presented): The apparatus according to claim 1 wherein the stop (13^v, 13^{vi}) is formed by the end of at least one elongated hole (13^v, 13^{vi}) of the bearing part (23) which is directed towards the axis of motion of the feed member (39) and the counterstop is formed by a dog pin (15) which is disposed transversely to the axis of motion in the feed member and

Application No. 09/980696
Page 7

Amendment
Attorney Docket No. H01.2I-10177-US01

traverses the elongated hole.

22. (Previously presented): The apparatus according to claim 1 wherein the bearing part (23) is associated with a detent (19 to 22) which after the hose (50) is clamped in place between the jaws (29) is releasable by a further advance of the feed member (39).

23. (Original): The apparatus according to claim 22 wherein the detent (19 to 22) has at least one arresting body (22) which, when in an arresting position, partly engages an receptacle (21) of the bearing part (23) and partly engages a counter-receptacle (20) and, when in a release position, only continues to engage the counter-receptacle (20).

24. (Original): The apparatus according to claim 23 wherein the arresting body is a cylindrical arresting pin (22) which when arrested, by a partial cross-section engages a partially cylindrical receptacle (21) of the bearing part (23) and by a partial cross-section engages a groove (20) as a counter-receptacle which is capable of accommodating the full cross-section of the arresting pin (22).

25. (Previously presented): The apparatus according to claim 23 wherein the arresting body (22) is forced by a spring (19) into the arresting position.

26. (Previously presented): The apparatus according to claim 23 wherein the spring is a spiral spring (19).

27. (Currently Amended): The apparatus according to claim 23 wherein the arresting body

Application No. 09/980696
Page 8

Amendment
Attorney Docket No. H01.2I-10177-US01

(22) is ~~adapted to~~ constructed and arranged to be moved out of its receptacle (21) in the bearing part (23) by means of a release (16) of the feed member (39)

28. (Original): The apparatus according to claim 27 wherein the release (16) has at least one surface (17) inclined obliquely to the forward feed axis for moving an arresting body (22) into the counter-receptacle (20) from its receptacle (21) in the bearing part (23).

29. (Previously presented): The apparatus according to claim 1 wherein the arresting body (22) is disposed on either side of the feed axis.

30. (Previously presented): The apparatus according to claim 23 wherein the two slide blocks (13) are associated with arresting bodies (22).

31. (Currently Amended): The apparatus according to claim 1 wherein the end support (34) has a bent-away fork head, a panel with a laterally opened receptacle (38) ~~or the like~~ for gripping behind a lug (53).

32. (Previously presented): The apparatus according to claim 1 which has a casing (6) comprising the drive (2).

33. (Previously presented): The apparatus according to claim 1 which has a tool head (1) carrying the inserted plier halves (24) on a casing (6).

34. (Previously presented): The apparatus according to claim 1 wherein the end support (34) is

Application No. 09/980696
Page 9

Amendment
Attorney Docket No. H01.2I-10177-US01

fixed to the tool head (1) ~~and/or the casing (6)~~.

35. (Previously presented): The apparatus according to claim 1 which has a control section including the control unit (3) ~~and/or the power supply unit~~.

36. (Previously presented): The apparatus according to claim 1 which is designed as a hand-held instrument.